

Technical Data

Rain Bird > Irrigation Programmers

> WPX



	mm
Hei.	103
Wid.	136
Dep.	62

Code	Type	Zone
OPG452	WPX-1	1
OPG453	WPX-2	2
OPG454	WPX-4	4
OPG455	WPX-6	6
OPG456	Wall mounting kit	



Wall mounting bracket

DESCRIPTION:

Features

- Its waterproof housing ensures a long service life even when installed in a valve box
- The most commonly used programming functions are easily accessible via screen that makes configuration simple and immediate
- Operation for approximately one year with 9 volt alkaline battery (type 6LR61) or for two years with two 9 volt alkaline batteries
- Large LCD display with intuitive user interface
- Sensor input with manual bypass exclusion
- Pump / Master Valve Start Circuit (Multi-Zone Units Only)
- Non-volatile programming memory (100 years)
- IP68 protection degree against the penetration of dust and water
- The programmer's plastic housing is ultra-resistant to atmospheric agents, yellowing and deterioration
- LCD screen size:
Width: 5,72 cm
Height: 3,18 cm
Weight: 907 g

Programming functions

- Dedicated manual watering button for intuitive operation
- Automatic prevention of zone overlap:
if the irrigation of several zones has been programmed at the same time, the WPX programmer will automatically irrigate the zone indicated with the lowest number first
- Contractor Rapid Programming™ feature automatically copies zone 1 start times and watering days to all other zones upon initial setup
- Watering times, start times and watering days are customizable by zone
- 6 start times per zone
- 4 watering day options per zone: custom days of the week, cyclical, ODD or EVEN calendar days
- Delayed irrigation (1 to 9 days)

Code	Description
OPG450	WPX-DV - Single station programmer kit - including WPX programmer and hydrovalve (DV Ø 1")