

Technical Data

Rain Bird > Accessories Programmers

> RSD-BEx Wired Rain Sensor



DESCRIPTION:

Features

- Automatic rain shutoff prevents overwatering due to natural precipitation
- Robust, reliable design reduces service call backs
- Moisture sensing disks work in a variety of climates
- Different sensor mounts permit speed and flexibility on the job site
- Latching hinge maintains alignment

Mechanical Properties

- Multiple rainfall settings from 5 - 20 mm are quick and easy with just the twist of a dial
- Adjustable vent ring helps control drying time
- High-grade, UV resistant polymer body resists the elements
- Comes with 5" latching aluminum bracket
- Not compatible with ESP-SMT or ESP-SMTe controllers

Electrical Specifications

- Application: Suitable for low voltage 24 V AC control circuits and 24 V AC pump start relay circuits (Not recommended for use with high voltage pump start, pump start relay circuits or devices)
- Switch electrical rating: 3A @ 125/250 V AC
- Capacity: Electrical rating suitable for use with up to ten 24 V AC, 7 VA solenoid valves per station, plus one master valve
- Wire: 7,6 m length of #20, 2 conductor UV resistant extension wire

Certifications

- cULus, CE, RCM

Dimensions

- Overall length: 16,5 cm
- Overall height: 13,7 cm
- Bracket hole pattern: 3,2 cm

Code	Description	Install.	Mod.
OSN013	RSD-BEX rain sensor	With 24 V AC and 9 V DC battery programmers	A61200