


Technical Data

Rain Bird > Sprays

> 1800 Series



Code	H	H ₁
OIS200	10	5
OIS202	15	10
OIS204	30	15
OIS205	15	10

1800 SERIES

Code	Body cm	Box*
OIS200	10	100
OIS202	15	75
OIS204	24	50

*Loose sprinklers on request

1800 SERIES/VALV. SAM

Code	Body cm	Box*
OIS205	15	75

*Loose sprinklers on request

1800 SAM PRS SERIES

Code	Model	Box*
OIS209	1804 SAM-PRS 2.1 - A37341	75
OIS210	1804 SAM-PRS 3.1 - A37441	75
OIS211	1806 SAM-PRS 2.1 - A37361	50
OIS212	1812 SAM-PRS 2.1 - A37321	50

*Loose sprinklers on request

DESCRIPTION:

1800 Series Features

- Co-molded wiper seal provides unmatched resistance to grit, pressure and the environment
- Constructed of time-proven UV-resistant plastic and corrosion resistant stainless steel parts, ensuring long product life
- Precision controlled flush at pop-down clears debris from unit, assuring positive stem retraction in all soil types
- Two-piece ratchet mechanism allows easy nozzle pattern alignment and provides added durability
- Five year trade warranty
- Operating Range:
 - spacing: 0,8 ÷ 7,3 m
 - pressure: 1,0 ÷ 4,8 bar

1800-SAM Series: Built-in Seal-A-Matic™ (SAM) check valve

- Eliminates the need for under-the-head check valves
- Traps water in lateral pipes in elevation changes of up to 4,2 m
- Reduces wear on system components by minimizing water hammer during start-up
- Operating Range:
 - spacing: 0,8 ÷ 7,3 m
 - pressure: 1,0 ÷ 4,8 bar

