

Technical Data

Hunter >

> X2 Programmers



	mm
Hei.	230
Wid.	190
Dep.	100

DESCRIPTION

Application

- Outdoor programmer, ready for internet, for residential systems

Features

- Number of stations: - 4, 6, 8, or 14 (fixed models)
- Wi-Fi capable controller automatically managed by Hydrowise® software
- Backlit display provides optimal visibility in any light
- 3 flexible programs with 4 start times each and up to 6-hour run times
- QuickCheck™ provides simple diagnostics of faulty field wiring
- Hide Programs option shows 1 program and 1 start time for simplification
- Suspend irrigation up to 99 days
- during the off-season
- Short-circuit protection detects wiring faults and skips the station without system damage
- Easy Retrieve™ memory backups the full irrigation schedule
- Delay Between Stations for slowclosing valves or pump recharge
- Cycle and Soak prevents water waste and runoff in areas with elevation changes or tight soils
- Seasonal adjustment for quicker schedule adjustments without changing run times

Features of the Wi-Fi module

- Provides rapid programming, online irrigation management, and controller status alerts
- Standard ABC programming with 6 programs and 6 start times or advanced schedules with 36 start times, and run times up to 24 hours
- Predictive Watering™ provides precise weather adjustments for maximum water savings
- Compatibility with Amazon Alexa™ and Control4® home automation

Specifics

- Transformer input: 120 V AC or 230 VAC
- Transformer output (24 V AC): 1 A
- Station output (24 V AC): 0,56 A
- P/MV output (24 V AC): 0,28 A
- Sensor inputs: 1
- Approvals (controller): Plastic IP44, UL, cUL, FCC, CE, RCM
- Approvals (module): Wi-Fi b/g/n, Bluetooth 5.0, CE, UL, RCM, FCC
- Warranty period: 2 years

Code	Description
OPG364	X2 programmer - 4 sectors
OPG365	X2 programmer - 6 sectors
OPG366	X2 programmer - 8 sectors
OPG367	X2 programmer - 12 sectors
OPG368	Wi-Fi Wand module



Wi-Fi Wand module

