

Technical Data

Hunter >

> HC Programmers



	mm
Hei.	152
Wid.	178
Dep.	33

DESCRIPTION

Application

- Perfect for residential projects, the indoor HC controller provides smart water savings and remote irrigation management capabilities.

Features

- Number of stations: – 6 or 12 (fixed indoor)
- Standard programming option allows for 6 independent irrigation programs and 6 start times per program
- Advanced programming option provides station-based programming with up to 6 total start times available
- 24-hour maximum station run time provides flexibility for low-flow zones
- 2 sensor inputs available for use with any Klik sensors and HC Flow Meter
- Station outputs can also be used to activate a pump start relay or master valve
- Wi-Fi enabled for quick connection to Hydrowise software
- 7 cm full-colour touchscreen display for simple programming at the control panel
- Built-in milliamp sensor for wire fault detection and alerts (12-station model only)

Specifics

- Transformer input: 120 V AC or 230 V AC
- Transformer output (24 V AC): 1 A
- Station output (24 V AC): 0,56 A
- P/MV output (24 V AC): 0,28 A
- Approvals: UL, cUL, FCC, CE, RCM
- Warranty period: 2 years

Code	Description
OPG582	Prog. HC Hydrowise ID - 6 sectors
OPG159	Prog. HC Hydrowise ID - 126 sectors
OPG160	Hydrowise + HC 12 sector module