

# Technical Data

Hunter >

## > HCC Programmers



Plastic	
	mm
Hei.	305
Wid.	350
Dep.	127

Metal	
	mm
Hei.	406
Wid.	330
Dep.	127

### DESCRIPTION

#### Application

- Programmer for residential, corporate and municipal systems
- Bring the power of Hydrowise® to residential, commercial, and public-sector projects with this affordable powerhouse

#### Features

- Number of stations:
  - Conventional: 8 to 38 (plastic), 8 to 54 (metal and pedestals)
- Standard programming option allows for 6 independent irrigation programs and 6 start times per program
- Advanced programming option provides station-based programming with up to 6 total start times available
- 24-hour maximum station run time provides flexibility for low-flow zones
- Any 2 programs or stations can operate simultaneously, providing more efficient watering
- 2 sensor inputs available for use with any Klik sensors and HC Flow Meter
- 1 P/MV output for pump start relay and master valve activation
- Wi-Fi enabled for quick connection to Hydrowise software
- 8 cm full-colour touchscreen display for simple programming at the control panel
- Built-in milliamp sensor for wire fault detection and alerts

#### Specifics

- Transformer input: 120/230 V AC
- Transformer output (24 V AC): 1,4 A
- Station output (24 VAC): 0,56 A
- P/MV output (24 VAC): 0,56 A
- Approvals: Plastic Wall Mount IP44, Plastic Pedestal IP34, NEMA 3R, UL, cUL, FCC, CE, RCM
- Warranty period: 5 years

Code	Description
OPG369	Prog. HCC plastic - 8 sectors
OPG370	Prog. Metal HCC - 8 sectors