

Technical Data

Hunter >



> Programmer Accessories - Roam Remote Control Systems



Transmitter and Receiver

	mm
Alt.	180
Lar.	60
Pro.	30

DESCRIPTION

Application

- Enable convenient controller management from a distance with this handheld wireless remote

Features

- Compatibility with Hunter X-Core™, X2™, Pro-C™, HPC, ICC2, HCC, I-Core™, ACC, and ACC2 controllers provides remote operation for projects of any size
- Manually start individual stations or programs for quick maintenance checks and troubleshooting
- 128 programmable addresses available prevents cross-communication between multiple remotes within close proximity of each other
- Programmable run times from 1 to 90 minutes, which will not overwrite regular automatic programming
- Manual operation up to 240 stations provides flexibility for larger projects

Specifics

- Range: 300 m from transmitter to receiver
- Transmitter power source: 4 x AAA batteries included
- Receiver power source: 24 V AC, 0,010 A
- System operating frequency: 433 MHz
- SmartPort™ installation: Maximum 15 m from controller
- FCC and CE approved for use in the United States and internationally
- Warranty period: 2 years

Code	Description
OPG373	Remote control system Roam Kit 300 mt
OPG374	Roam receiver 300 mt

> Programmer Accessories - Roam XL Remote Control Systems



Transmitter and Receiver

	mm
Alt.	160
Lar.	80
Pro.	30

DESCRIPTION

Application

- Add professional, licence-free remote control to projects of any size with this long-range remote

Features

- Compatibility with Hunter X-Core™, X2™, Pro-C™, HPC, ICC2, HCC, I-Core™, ACC, and ACC2 controllers provides remote operation for a wide variety of landscapes
- Manually start individual stations or programs for quick maintenance checks and troubleshooting
- 128 programmable addresses available prevents cross-communication between multiple remotes within close proximity of each other
- Programmable run times from 1 to 90 minutes, which will not overwrite regular automatic programming
- Manual operation up to 240 stations provides flexibility for larger projects
- Rugged and water-resistant transmitter includes a large LCD display with simple push-button operation and a battery-life indicator

Specifics

- Range: 3 km (line of sight) from transmitter to receiver
- Transmitter power source: 4 x AAA batteries included
- Receiver power source: 24 V AC, 0,010 A
- System operating frequency: 27 MHz
- SmartPort™ installation: maximum 15 m from controller
- FCC approved (not available in EU and some other countries, check local regulations)
- Warranty period: 3 years

Code	Description
OPG375	Roamxl Kit 3 km remote control system
OPG376	Roam xl receiver 3 km