


Technical Data

Toro >

> T5P-RS Series Rotors



DESCRIPTION:

Dimensions

- Diameter of the nozzle holder: 57 mm

- Ring nut diameter: 67 mm

Technical specifications

- Radius: 7,6 ÷ 15,2 m
- From the top: 40 ÷ 360°
- Flow range: 2,8 ÷ 36,5 l/min
- Operating pressure range: 1,7 ÷ 4,8 bar

- Trajectory angle: 25° standard, 10° low trajectory
- Connection F: 3/4"
- Nozzle No. 3,0 pre-installed

Features and Benefits

- **Standard rubber protective coating**
The protective rubber coating on the top of the sprinkler reduces impact injuries and liability
- **Complete set of nozzles**
Model T5 includes a full set of nozzles: eight standard nozzles (25°) and four low trajectory nozzles (10°)
- **Optional check valve**
Available with a holding force of 2,1 m elevation gain

- **Adjustment of the working angle from the top**
Changing the working angle of the T5 can be done from the top between a minimum of 40° and full circle 360° - The working angle is changed from the top with a small flat screwdriver, with the turret out or returned.
- **RapidSet™ working angle adjustment**
Easy adjustment of the working angle, without the use of tools and without the risk of over-torque or damaging the inside of the rotor

Available options

- Check valve

Code	Description	Box
OID607	T5P-RS series P = Lawn Pop-up RS = RapidSet	20

PERFORMANCE TABLE

Nozzle	Pressure bar	Radius m	Flow rate l/min	Precipitation mm/h		Nozzle mm	Pressure bar	Radius m	Flow rate l/min	Precipitation mm/h	
				■	▲					■	▲
1,5	1,7	10,06	4,4	5,16	5,96	4,0	1,7	11,28	11,2	10,54	12,17
1,5	2,0	10,18	4,7	5,44	6,29	4,0	2,0	11,64	12,1	10,69	12,34
1,5	2,5	10,40	5,3	5,90	6,82	4,0	2,5	12,27	13,7	10,92	12,61
1,5	3,0	10,62	5,9	6,27	7,25	4,0	3,0	12,71	15,2	11,30	13,04
1,5	3,5	10,67	6,3	6,69	7,73	4,0	3,5	12,80	16,3	11,92	13,77
1,5	4,0	10,76	6,7	6,99	8,07	4,0	4,0	12,89	17,3	12,49	14,42
1,5	4,5	10,97	7,1	7,09	8,19	4,0	4,5	13,11	18,4	12,83	14,81
2,0	1,7	10,67	5,5	5,79	6,68	5,0	1,7	11,89	14,2	12,05	13,92
2,0	2,0	10,79	6,0	6,20	7,16	5,0	2,0	12,13	15,3	12,50	14,44
2,0	2,5	11,01	7,0	6,89	7,96	5,0	2,5	12,57	17,3	13,15	15,18
2,0	3,0	11,23	7,8	7,46	8,62	5,0	3,0	13,02	19,0	13,44	15,51
2,0	3,5	11,28	8,4	7,94	9,17	5,0	3,5	13,46	20,7	13,73	15,86
2,0	4,0	11,28	9,0	8,52	9,83	5,0	4,0	13,72	22,2	14,14	16,33
2,0	4,5	11,28	9,8	9,21	10,64	5,0	4,5	13,72	23,1	14,73	17,01
2,5	1,7	10,67	6,6	6,98	8,07	6,0	1,7	11,89	15,9	13,50	15,59
2,5	2,0	10,79	7,3	7,53	8,70	6,0	2,0	12,38	17,4	13,65	15,76
2,5	2,5	11,01	8,5	8,41	9,71	6,0	2,5	13,22	20,1	13,79	15,92
2,5	3,0	11,23	9,5	8,99	10,39	6,0	3,0	13,88	22,4	13,96	16,12
2,5	3,5	11,28	10,2	9,62	11,11	6,0	3,5	14,20	24,2	14,42	16,65
2,5	4,0	11,28	10,9	10,27	11,86	6,0	4,0	14,42	25,9	14,93	17,24
2,5	4,5	11,28	11,5	10,89	12,58	6,0	4,5	14,63	27,4	15,39	17,77
3,0	1,7	10,97	8,3	8,30	9,58	8,0	1,7	10,97	21,8	21,69	25,05
3,0	2,0	11,22	8,9	8,52	9,84	8,0	2,0	11,83	23,8	20,43	23,59
3,0	2,5	11,66	10,1	8,88	10,25	8,0	2,5	13,26	27,3	18,65	21,54
3,0	3,0	12,10	11,3	9,25	10,68	8,0	3,0	14,14	29,9	17,96	20,74
3,0	3,5	12,19	12,6	10,15	11,72	8,0	3,5	14,50	32,4	18,51	21,37
3,0	4,0	12,19	13,6	11,01	12,72	8,0	4,0	14,81	34,7	18,99	21,93
3,0	4,5	12,19	14,4	11,61	13,41	8,0	4,5	15,24	36,7	18,97	21,91

Data based on 180°