

# Technical Data

## Toro > Sensors

### > Rain Cable



	mm
Hei.	89
Wid.	44
Dep.	44

Code	Description
OSN009	Rain sensor with preinstalled cable L= 8 m

#### DESCRIPTION:

- Sometimes, when it rains, all you need is a simple sensor to ensure precise work
- With various parameters for adjusting the perception of rain


#### Application

and hygroscopic disks that do not require maintenance, the OSN009 model guarantees the necessary reliability


#### Technical specifications and exclusive features

- Relay contact output, normally open or normally closed: 3 A, 24 V AC
- Operating temperature:  $-28^{\circ}\text{C} \div 49^{\circ}\text{C}$
- Small size and UV resistant cabinet for the sensor
- No special tools are required for installation
- Compatible with all Toro and other brand programmers
- Universal operation normally open and normally closed for compatibility with all programmers designed for use with a sensor
- The hygroscopic disks do not require maintenance
- Uses standard industrial grade hygroscopic disks, with selectable parameters adjustable to 3, 6, 13 and  $\frac{3}{4}$ " of rain
- 7,6 m of UV resistant cable
- Includes 7,6m of white UV resistant outdoor cable
- Weight: 0,4 kg product and carton


#### Three mounting options



Quick mounting bracket on the gutter



Quick wall mounting bracket



Pipe adapter