


# Technical Data

Weathermatic >

> MAXSpray Series



| Model | H    | H <sub>1</sub> |
|-------|------|----------------|
| MAX4  | 15,9 | 10             |
| MAX6  | 21,6 | 15             |
| MAX12 | 38,7 | 30             |



MAX4

MAX6

## DESCRIPTION:

- Standard white Santoprene seal for exceptional performance
- The first gasket, turret and double pressure cap eliminate cap-to-body leaks
- Strong spring to allow an efficient return of the turret; made of corrosion resistant stainless steel for long life
- Self-cleaning control valve with resistance to debris across



## Features

- an extensive surface
- Tapered design to facilitate self-cleaning operations
- Good seal even in dirty water environments
- Low profile, easy-to-pull flat plug and drain plug for sprinkler leveling
- Pressure range: 1,0 ÷ 4,8 bar
- Female threaded connection 0 1/2"

| Code   | Article | Box |
|--------|---------|-----|
| OIS030 | MAX4    | 50  |
| OIS031 | MAX6    | 50  |

Note: 5 years guarantee

## STATIC SPRINKLER ACCESSORIES

| Code   | Article | Description         | Box |   |
|--------|---------|---------------------|-----|---|
| OIS059 | MAX-EXT | 6P extension for LX | 100 |  |
| OIS060 | MAXS    | 1/2" shrub adapter  | 25  |  |