

Technical Data

Valticino >

> YL-21055 Programmer



DESCRIPTION:

Application

- Single outlet tap control unit

Specifications

- Control unit power supply: batteria 3 V (2 x 1,5 AA)
- Degree of protection: IP65
- Built-in on/off valve
- Thread: in/out 3/4" M/M
- Maximum working pressure: 6 bar
- Maximum range: 1.000 l/h

Features

- LCD display display
- Rotor selection functions
- Command keys
- Irrigation time: from 5 sec to 360 min
- Frequency from 10 sec to 7 days
- Rain sensor settable
- Predisposition for rain sensor or humidity sensor

Code	Model	Ø valves
OPG500	YL21055	3/4"

> YL-21068 Programmer



DESCRIPTION:

Application

- Double outlet tap control unit

Specifications

- Control unit power supply: 3 V (2 x 1.5 AA) battery
- Degree of protection: IP65
- Built-in on/off valve
- Thread: in/out 3/4" M/M
- Maximum working pressure: 6 bar
- Maximum range: 1.000 l/h

Features

- LCD display display
- Rotor selection functions
- Command keys
- Irrigation time: from 5 sec to 360 min
- Frequency from 10 sec to 7 days
- Rain sensor settable
- Predisposition for rain sensor or humidity sensor

Code	Model	Ø valves
OPG501	YL21068	3/4"

> Sensors

Code	Model	Description	
OPG504	YL21103	Rain sensor - 5 mt cable	
OPG505	YL21106	Humidity sensor - 5 mt cable	