

Technical Data

Special Pipe >

> Drainage

DESCRIPTION:

Double-Wall PEAD

- Draining systems

Nude PVC

- Rigid, corrugated and flexible PVC
- Standard holes width is 1,3 mm and this is excellent in order to avoid cloggings
- The ring shape allows a high crushing resistance (on normal conditions, can be put underground up to a 5 mt depth)

Coated PVC

- Aspirations and pourings of food and no-food waters and liquids
- Atoxic, light, flexible and plasticised PVC, with rigid, anti-shock and anti-crashing PVC reinforce spiral
- Working temperature: $-15^{\circ}\text{C} \div +60^{\circ}\text{C}$
- Colour: transparent with ivory spiral

Double-Wall PEAD			Nude PVC			Coated PVC		
								
Ø	Code	mt	Ø	Code	mt	Ø	Code	mt
63	TDR530	50	50	TDR002	240	50	TDR011	200
75	TDR531	50	65	TDR003	150	65	TDR012	150
90	TDR532	50	80	TDR005	100	80	TDR013	100
110	TDR533	50	100	TDR006	50	100	TDR014	50
125	TDR534	50	125	TDR007	50			
160	TDR536	50	160	TDR009	50			
200	TDR537	25	200	TDR008	40			